



■ Safe Care Supersolv

- Is a non-evaporative solvent that safely removes most organic and inorganic soils without damaging the cleaning surface.
- With a Kauri Butinol (KB) value estimated in excess of 150, Safe Care SuperSolv removes lubricants, brake fluid, engine oil, lithium grease, paint, permanent marker, and certain adhesives.
- Safe Care SuperSolv is non-aromatic and contains no ozone depleting chemicals.
- Safe Care SuperSolv is an organic, antioxidant solvent that will not harm most plastics, vinyl, nylon, butene, rubber, ferrous metals or natural fibers.

■ Use

- Safe Care Supersolv is water miscible and works effectively in ultrasonic cleaners and automatic parts cleaners.

■ Use Instructions

- It is a powerful solvent and should be pre-tested prior to use especially on soft metals.
- It may be used full-strength or diluted with water depending on the specific application. When water is added, Safe Care SuperSolv will become more of a release agent and less of a solvent.
- It may be spray applied, or applied by a cloth, and wiped from the cleaning surface.
- Rinse thoroughly with water to remove soil and residual product.
 - Suggested dissolution: Heavy Cleaning: 100% - 50%, Average Cleaning: 50% - 20%, Routine Maintenance: 10% - 2%

■ Basic Properties:

- | | |
|---|--|
| ■ Appearance: Clear, viscous light amber liquid | ■ Flash Point: 82.2°C (180°F) |
| ■ Odor: Mild solvent | ■ Specific Gravity: 1.018 gm/cc |
| ■ Water Solubility: 100% | ■ Relative Density: Greater than water |
| ■ Boiling Point: 136.6°C (212°F) | ■ pH Range: 10.2 – 10.4 |

■ Safe Care Supersolv:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

■ Safe Care Supersolv do not contain:

- Petroleum distillates
- Glycol ethers
- Terpenes
- Synthetics
- Caustics
- Builders & reagents

■ Certifications

- OSHA 29-CFR Ch. XVII 1910.1200 and 40 CFR Ch. 1, Subparts C&D
- USEPA 600, 4-90, 027 for aquatic toxicity
- USEPA 601 & 602 for VOC testing
- GSA SIN 375-361, 375-362 & 375-363
- US DOT: Class 55, Liquid Cleaning Compounds

■ Powerful replacement of:

- | | |
|-------------------------|---------------------|
| ■ 1,1,1-Trichloroethane | ■ Butyl Cellosolve |
| ■ TCA | ■ Trichloroethylene |
| ■ Toluene | ■ TCE |
| ■ Methyl benzene | ■ Perchloroethylene |
| ■ Methyl Chloride | ■ Stoddard Solvent |
| ■ Glycol Ethers | |

All of our products are natural and certified:



🏠 SPAIN

E: ump@ump-spain.com
T: +34 942 360 472

UMP SPAIN
C/Juan de Herrera 2, 1ºD, 39002, Santander

🏠 FRANCE

E: umpfrance@ump-spain.com
T: +34 609 481 130

UMP FRANCE
Parque tecnológico de Zamudio, Laga Bidea, Ed. 84
48160, Derio (España)
Château de Véretz, 37270, Véretz (Francia)