

■ Safe Care Graffiti, Tar & Gum Remover

- Derived from 100% plant-based materials, SC-Graffiti, Tar & Gum Remover effectively removes most organic and inorganic soils without harming the cleaning surface.
- It is a world-wide recognized product for its high-tech for anti-vandalism.

■ Use

- SC-Graffiti, Tar & Gum Remover is a powerful non-evaporative solvent intended to loosen tough soils such as tar, chewing gum, permanent marker, ink and graffiti paints.

■ Use Instructions

- When removing grease, tar, gum, or similar materials from carpeting or upholstery fabrics, begin by scraping off any loose material with the edge of a spatula-like tool.
- Apply a small amount of the product and allow to dwell for 5 to 10 minutes before agitating with a nylon brush.
- For best results, rinse soil and residual product with an aqueous cleaning solution (SC-1000).
- Warning: Pre-test small inconspicuous area before applying. SC-Graffiti, Tar & Gum Remover should not be left on surfaces for a prolonged period of time because it will remove most paints or may damage some acrylic surfaces.

■ Basic Properties:

- | | |
|--|-------------------------------------|
| ■ Appearance: Clear, slightly viscous light yellow | ■ Flash Point: 65.5°C (150oF) |
| ■ Odor: Distinctive, mild | ■ Specific Gravity: 0.946 gm/cc |
| ■ Water Solubility: Not water soluble | ■ Relative Density: Less than water |
| ■ Boiling Point: 144.4°C (292°F) | ■ pH Range: 6.9 |

■ Safe Care Graffiti, Tar & Gum Remover:

- Non-toxic
- Non-reactive
- Non-carcinogenic
- Readily biodegradable
- Derived from renewable resources
- Safe to use, store and dispose of

■ SC - Graffiti, Tar & Gum Remover do not contain:

- Petroleum distillates
- Glycol ethers
- Terpenes
- Synthetics
- Caustics
- Builders & reagents

■ Certifications

- OSHA 29-CFR Ch. XVII 1910.1200 and 40 CFR Ch. 1, Subparts C&D
- USEPA 600, 4-90, 027 for aquatic toxicity
- USEPA 601 & 602 for VOC testing
- GSA SIN 375-362 & 375-363

■ Powerful replacement of:

- Xylene
- Toluene
- Methyl benzene
- Methyl Ethyl Ketone
- Glycol Ethers
- Butyl Cellosolve
- Kerosene
- Mineral Oil

All of our products are natural and certificated:



🏠 SPAIN

E: ump@ump-spain.com
T: +34 942 360 472

UMP SPAIN
C/Juan de Herrera 2, 1ºD, 39002, Santander

🏠 FRANCE

E: umpfrance@ump-spain.com
T: +34 609 481 130

UMP FRANCE
Parque tecnológico de Zamudio, Laga Bidea, Ed. 84
48160, Derio (España)
Château de Vétetz, 37270, Vétetz (Francia)